

# PowerUp RCL.1000

The Heavy Duty Lubricator for serious tools boxes.  
Stays where you spray with polarized film.

**RCL 1000:** All purpose lubricating fluid can be used on sliding doors, hinges, bicycles, locks, sewing machines, air tools, etc.

<b>PART#:</b>	<b>3500-17-1 (482ml)</b>	<b>3500-4-4 (4L x4)</b>
	<b>3500-17-12 (482ml x12)</b>	<b>3500-20-1 (20L pail)</b>
	<b>3500-750-1 (750ml)</b>	<b>3500-205-1 (205L drum)</b>
	<b>3500-750-4 (750ml x4)</b>	
	<b>3500-4-1 (4L)</b>	

### DESIGNED FOR PERFORMANCE

- Specifically designed for thin film, heavy load lubrication applications
- Reduces friction and drag by forming a high strength boundary film
- Speeds up drilling and tapping; cutting edges remain sharper longer
- Prolongs operating life
- Resists rust and corrosion
- Displaces water, inhibiting oxidation (rust)
- Will not tarnish metals
- Designed to withstand corrosive environments
- Compatible with typical seals except EPDM
- Apply with a spray or a brush between rubbing surfaces

TYPICAL PROPERTIES	ASTM METHOD	Needle Oiler
Appearance		Clear, Dark, Amber
Color	ASTM D1500	2.3
Flash Point	ASTM D92	130°C
Pour Point	ASTM D97	-36°C
Fire Point	ASTM D92	135°C
Viscosity @ 40°C (cSt)	ASTM D445	8 cSt
Specific Gravity	D445	0.860
Density @ 20°C	ASTM D941	0.860 g/mL

